




# UGY10LK1

## UNIVPOWER SILENT SERIES

### POWER OUTPUT

Prime Rating — 8 kW (8 kVA)  
 Standby Rating — 10 kW (10 kVA)  
 Single-Phase, 60 Hertz, 1.0 PF



### STANDARD FEATURES


- Heavy duty, 4-cycle, variable speed fan, diesel engine provides maximum reliability.
- Brushless alternator reduces service and maintenance requirements. Class H protection.
  - Open delta alternator design provides virtually unlimited excitation for maximum motor starting capability.
  - Automatic voltage regulator (AVR) provides precise regulation.
- Electronic governor system maintains frequency to  $\pm 0.25\%$ .
- Full load acceptance of standby nameplate rating in one step
- Soundproof, weather resistant, steel housing provides operation at 62dB (A) at 7meters. Fully lockable enclosure allows safety operation. Outdoor operation available.
- Internal fuel tank with direct observing glass, and fuel level meter display on control panel  
 E-coat and powder coat paint provides durability and weather protection.
- Digital engine gauges including oil pressure, water temperature, battery volts, engine speed, and fuel level.
- Analog generator instrumentation including Ampere meter,
- Voltage meter, frequency meter, ammeter phase selector switch, voltmeter phase selector switch. Analog generator instrumentation and regulator adjustment.
- Deepsea/Comap professional generator controller.
  - High visibility LCD display with heated screen and alphanumeric readout.
  - IP65 Protection standard, operational temperature range of -40° to 85° C.
  - Modbus interface for gauge panel and expansion options.
  - DPF cleaningcycle indication.
  - Log record for inspection
- Automatic safety shutdown system monitors the water temperature, engine oil pressure, low coolant, low DEF, overspeed, and overcrank. Warning lights indicate abnormal conditions.
- Fuel/water separator. Removes condensation from fuel for extended engine life.
- Emergency stop switch — when manually activated, shuts down in any emergency.

### UNIVPOWER SILENT SERIES

| UNIV POWER DECIBELLEVELS  |   |
|---|---|
| Revolving field, self ventilated weatherproof Normal conversation allows substantially lower operating noise levels than competitive designs. UNIV Gensets good for home, construction sites, residential, hospital, etc. | <ul style="list-style-type: none"> <li>90 — Subway / truck traffic</li> <li>80 — Average city traffic</li> <li>70 — Inside car at 60 mph</li> <li>→ UNIVGenset at 7m</li> <li>60 — Air conditioner at 6m</li> <li>50 — Normal conversation</li> </ul> |

**60.0**  
DECIBELS

### GENERATOR OUTPUT PANEL





# UGY10LK1

## UNIVPOWER SILENT SERIES

### SPECIFICATIONS

| Generator Specifications                   |  |
|--|--|
| Model                                      | Revolving field, self-ventilated weatherproof                      |
| Armature Connection                        | Star with Neutral  |
| Phase                                      | 1  |
| Standby Output                             | 10KW (10KVA)   |
| Prime Output                               | 8 KW (8 KVA)   |
| Power Factor                               | 1.0  |
| Voltage Regulation (No load to full load)  | ±0.5%  |
| Generator RPM                              | 1800   |
| Frequency                                  | 60 Hz  |
| No. of Poles                               | 4  |
| Excitation                                 | Brushless with AVR   |
| Frequency Regulation: No Load to Full Load | Isochronous under varying loads from no load to 100% rated load    |
| Frequency Regulation: Steady State         | ±0.25% of mean value for constant loads from no load to full load. |
| Insulation                                 | Class H  |
| Sound Level dB(A) Full load at 7M          | 60   |

| Amperage                                    |              |
|---|--------------|
| Rated Voltage                               | Maximum Amps |
| 1Ø Volt 110/220                             | 54.5 Amps    |
| Main Line Circuit Breaker Rating            | 63 Amps      |
| Over Current Relay Trip Set Point 220V Mode | 70 Amps      |

| Fuel System                  |                           |
|------------------------------|---------------------------|
| Maximum Fuel Flow (per hour) | 1.27 gallons (4.8 liters) |
| Fuel Tank Capacity           | 14.8 gallons (56 liters)  |
| Fuel Consumption             | L / h                     |
| At full load                 | 2.4                       |
| At 3/4 load                  | 1.9                       |
| At 1/2 load                  | 1.5                       |
| At 1/4 load                  | 1.3                       |

| Control system     |                               |
|--------------------|-------------------------------|
| Controller Brand   | Smartgen                      |
| Model              | HGM420N                       |
| Module             | Manual/Auto start/stop module |
| Standard function  | Engine control                |
|                    | Generator monitoring          |
|                    | Generator protection          |
|                    | Specification                 |
| Display            | Frequency                     |
|                    | Battery voltage               |
|                    | Running hour                  |
| Warning/shutdown   | under/over voltage            |
|                    | under/over speed              |
|                    | under/over frequency          |
|                    | Low oil pressure              |
|                    | High water temperature        |
| Communication port | USB                           |

| Engine Specifications     |   |
|---------------------------|---|
| Make / Model              | LD/ KM385BD   |
| Emissions                 | /   |
| Starting System           | Electrical start  |
| Design                    | 3 cylinder, 4-cycle, water cooled, direct injection, natural intake |
| Displacement              | 1.5 liters  |
| No. cylinders             | 3   |
| Bore x Stroke             | 85*90mm   |
| Gross Engine Power Output | 17.7hp (13.2 kW)  |
| Compression Ratio         | 23:1  |
| Engine Speed              | 1800 rpm  |
| Overspeed Limit           | 2070 rpm  |
| Oil Capacity              | 2.35 gallons (8.9 liters)   |
| Coolant Capacity          | 1.46 gallons (5.5 liters)   |
| Battery                   | 12V 60Ah x 1  |

| Alternator                      |                                |
|---------------------------------|--------------------------------|
| Alternator Brand                | KWISE                          |
| Alternator Model                | S164G88B2                      |
| Excitation                      | Brushless, Self-Excited system |
| Capacity(KVA)                   | 10kva                          |
| Power(KW)                       | 10kw                           |
| Efficiency(%)                   | 80%                            |
| Insulation class                | Class H                        |
| Protection class                | Ip23                           |
| Steady state voltage regulation | ±1%                            |
| Voltage control                 | AVR                            |

### WARRANTY\*

#### Generator

12 months from date of purchase or 1000 running hours (whichever occurs first)



### NOTICE

Enough Air flow is extremely important to Generator operation. Improper connection can cause electrocution and/or property damage. Do not connect to any electrical system except through an approved device. Specifications are subject to change without notice.




# UGY10LK1

## UNIVPOWER SILENT SERIES



| Weight                      |         |
|-----------------------------|---------|
| Dry Weight                  | 560 kg  |
| Wet Weight                  | 600kg   |
| Max. Lifting Point Capacity | 1000 kg |



Manufactured by  
**Zhejiang Universal Machinery Co.,Ltd**  
Add:No 18-9 Nanshan Road, Qujiang Zone,  
Quzhou city, Zhejiang Province, CN  
Tel:0086-570-3377085  
Fax:0086-570-3377086  
Website:www.univpower.com